


Working temperature:  $0 \div 80 \, ^{\circ}\text{C}$ Rope lenght: about 3 m Pulses / shift lenght:  $1 / 25 \, \text{mm}$ Contact type: Normally Closed

 $\begin{array}{lll} \text{Contact resistance:} & 6 \ \Omega \\ \text{Pulse duration:} & 5 \div 8 \ \text{ms} \\ \text{Max current:} & 20 \ \text{mA} \\ \text{Max voltage:} & 100 \ \text{V} \\ \end{array}$ 

#### RESPECT THE POLARITY INDICATED ON PRODUCT

For series connection follow nect scheme:



# ATEL Piezo-electric roller detector




Working temperature:  $0 \div 80 \, ^{\circ}\text{C}$ Rope lenght: about 3 m Pulses / shift lenght:  $1 / 25 \, \text{mm}$ Contact type: Normally Closed

Contact resistance:  $6 \Omega$ Pulse duration:  $5 \div 8 \text{ ms}$ Max current: 20 mAMax voltage: 100 V

## **RESPECT THE POLARITY INDICATED ON PRODUCT**

For series connection follow nect scheme:



# ATEL

Piezo-electric roller detector




Working temperature:  $0 \div 80 \,^{\circ}\text{C}$ Rope lenght: about 3 m Pulses / shift lenght:  $1 / 25 \,^{\circ}$ mm Contact type: Normally Closed

Contact resistance:  $6 \Omega$ Pulse duration:  $5 \div 8 \text{ ms}$ Max current: 20 mAMax voltage: 100 V

### RESPECT THE POLARITY INDICATED ON PRODUCT

For series connection follow nect scheme:



# **ATEL**

Piezo-electric roller detector




Working temperature:  $0 \div 80 \,^{\circ}\text{C}$ Rope lenght: about 3 m Pulses / shift lenght:  $1 / 25 \,^{\circ}$ mm Contact type: Normally Closed

 $\begin{array}{lll} \text{Contact resistance:} & 6 \ \Omega \\ \text{Pulse duration:} & 5 \div 8 \ \text{ms} \\ \text{Max current:} & 20 \ \text{mA} \\ \text{Max voltage:} & 100 \ \text{V} \\ \end{array}$ 

## RESPECT THE POLARITY INDICATED ON PRODUCT

For series connection follow nect scheme:





Piezo-electric roller detector




Working temperature: 0 ÷ 80 °C
Rope lenght: about 3 m
Pulses / shift lenght: 1 / 25 mm
Contact type: Normally Closed

Contact resistance:  $6 \Omega$ Pulse duration:  $5 \div 8 \text{ ms}$ Max current: 20 mAMax voltage: 100 V

#### RESPECT THE POLARITY INDICATED ON PRODUCT

For series connection follow nect scheme:





Piezo-electric roller detector



Working temperature:  $0 \div 80 \,^{\circ}\text{C}$ Rope lenght: about 3 m Pulses / shift lenght:  $1 / 25 \,^{\circ}$ mm Contact type: Normally Closed

Contact resistance:  $6 \Omega$ Pulse duration:  $5 \div 8 \text{ ms}$ Max current: 20 mAMax voltage: 100 V

#### RESPECT THE POLARITY INDICATED ON PRODUCT

For series connection follow nect scheme:

